

SAFETY DATA SHEET ACCORDING TO REGULATION (EC) 1907/2006

Product name: Stonder Plastic Primer Plus

Creation date: 16.03.2023, Revision: 15.05.2023, version: 2.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name

Stonder Plastic Primer Plus

Product code

[80120,80151 UFI:2PV4-074F-Y00K-4WRW]



<https://my.chemius.net/p/KeuW19/en/pd/en>

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Primer for plastics. For professional use in car refinishing.

Uses advised against

The product should not be used in ways other than those referred to in Section 1.

1.3 Details of the supplier of the safety data sheet

Supplier

Rags LTD

Džūkstes str.1

LV-1004 Rīga, Latvia

+37167808780

rags@rags.lv

1.4 Emergency Telephone Number

Emergency

112

Supplier

+37167808780

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Acute Tox. 4; H312 + H332 Harmful in contact with skin or if inhaled.

Skin Irrit. 2; H315 Causes skin irritation.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H335 May cause respiratory irritation.

STOT RE 2; H373 May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

**Signal word: DANGER**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 + H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulation.

Contains:

xylene

ethylbenzene

2.3 Other hazards**PBT/vPvB**

No information.

Endocrine disrupting properties

No information.

Additional information

No information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substances**

For mixtures see 3.2.

3.2 Mixtures

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Concentration Limits	Notes for substances
xylene	1330-20-7 215-535-7 601-022-00-9	60-80	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 + H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373	/	C
ethyl acetate	141-78-6 205-500-4 607-022-00-5	10-18	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	/	/
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35- XXXX	10-15	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373 Aquatic Chronic 3; H412	/	/

chlorobenzene	108-90-7 203-628-5 602-033-00-1	<0,2	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Acute Tox. 4; H332 Aquatic Chronic 2; H411	/	/
---------------	---------------------------------------	------	--	---	---

Notes for substances

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
---	---

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. When it is suspected, that there may still be harmful vapours/fumes present in the air, respiratory protection (mask; self contained breathing apparatus) must be used. Wash contaminated clothing with water before removing or use gloves.

Following inhalation

Remove patient to fresh air - move out of dangerous area. In case of unconsciousness bring patient into stable side position and seek medical attention. If breathing is irregular or respiratory arrest occurs provide artificial respiration. Keep at rest in a position comfortable for breathing. Seek medical help immediately.

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. Consult a physician.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. Seek medical help.

Following ingestion

Do not induce vomiting! Aspiration hazard if swallowed. Can enter lungs and cause damage. If vomiting occurs, the patient should hold the head lower than the hips, because it reduces the possibility of aspiration. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation

Can cause irritation of respiratory system. Symptoms include: headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Coughing, sneezing, nasal discharge, labored breathing. Harmful.

Following skin contact

Itching, redness, pain. Harmful.

Following eye contact

Redness, tearing, pain.

Following ingestion

May cause nausea/vomiting and diarrhea. May cause abdominal discomfort. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area. Aspiration into the lungs causes coughing, shortness of breath and may

lead to chemical pneumonia.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. After the product has been ingested vomiting can cause aspiration into the lungs. Because of the risk of aspiration, induction of vomiting and gastric lavage should be avoided.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

5.3 Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. No action shall be taken involving any personal risk or without suitable training. Prolonged heating can cause an explosion. Vapours can form explosive mixtures with air. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (BS EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (BS EN 137).

Additional information

No information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment

No information.

Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

Emergency procedures

No action shall be taken involving any personal risk or without suitable training. Prevent access to unprotected personnel. Evacuate the danger zone. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing.

For emergency responders

Use personal protective equipment.

6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. In case of release into the environment, inform the relevant authorities.

6.3 Methods and material for containment and cleaning up

For containment

Stem the spill if this does not pose risks.

For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Use only explosion-proof instruments and equipment. Use spark-proof tools. Prevent release into the sewer, water, basements or confined areas. Ventilate the premises. Clean contaminated area with plenty of water.

OTHER INFORMATION

No information.

6.4 Reference to other sections

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Vapours are heavier than air and spread along the floor. They form explosive mixtures with air.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

Other measures

No information.

Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin, eyes and clothes. Remove contaminated clothes and wash them before reuse. Wear suitable protective equipment; see Section 8.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep in a cool, dry and well ventilated place. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising substances. Keep away from sources of ignition - no smoking.

Packaging materials

Store only in original container.

Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

Storage class

No information.

Further information on storage conditions

No information.

7.3 Specific end use(s)

Recommendations

No information.

Industrial sector specific solutions

No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure limit values

Name	mg/m ³	ml/m ³	Short-term value mg/m ³	Short-term value ml/m ³	Remark	Biological Tolerance Values
Ethylbenzene (100-41-4)	441	100	552	125	Sk	/
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	220	50	441	100	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift 650 mmol methyl hippuric acid/mol creatinine in urine - Post shift 650 mmol methyl hippuric acid/mol creatinine in urine - Post shift
Chlorobenzene (108-90-7)	4.7	1	14	3	Sk	5 mmol 4-chlorocatechol/mol creatinine in urine - Post shift
Ethyl acetate (141-78-6)	734	200	1468	400	/	/

Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

DNEL/DMEL values

For product

No information.

For components

Name	Type	Exposure route	exp. frequency	Remark	value
ethyl acetate	Worker	inhalation	long term systemic effects	/	734 mg/m ³
ethyl acetate	Worker	inhalation	short term systemic effects	/	1468 mg/m ³
ethyl acetate	Worker	inhalation	long term local effects	/	734 mg/m ³
ethyl acetate	Worker	inhalation	short term local effects	/	1468 mg/m ³
ethyl acetate	Worker	dermal	long term systemic effects	/	63 mg/kg bw/day
ethyl acetate	Consumer	inhalation	long term systemic effects	/	367 mg/m ³
ethyl acetate	Consumer	inhalation	short term systemic effects	/	734 mg/m ³
ethyl acetate	Consumer	inhalation	long term local effects	/	367 mg/m ³
ethyl acetate	Consumer	inhalation	short term local effects	/	734 mg/m ³
ethyl acetate	Consumer	dermal	long term systemic effects	/	37 mg/kg bw/day
ethyl acetate	Consumer	oral	long term systemic effects	/	4.5 mg/kg bw/day
chlorobenzene	Worker	inhalation	long term systemic effects	/	23 mg/m ³
chlorobenzene	Worker	inhalation	short term systemic effects	/	70 mg/m ³
chlorobenzene	Worker	dermal	long term systemic effects	/	5 mg/kg bw/day

chlorobenzene	Worker	dermal	short term systemic effects	/	15 mg/kg bw/day
chlorobenzene	Consumer	inhalation	long term systemic effects	/	1 mg/m ³
chlorobenzene	Consumer	inhalation	short term systemic effects	/	1 mg/m ³
chlorobenzene	Consumer	dermal	long term systemic effects	/	3 mg/kg bw/day
chlorobenzene	Consumer	dermal	short term systemic effects	/	3 mg/kg bw/day
chlorobenzene	Consumer	oral	long term systemic effects	/	3 mg/kg bw/day
chlorobenzene	Consumer	oral	short term systemic effects	/	3 mg/kg bw/day

PNEC values

For product

No information.

For components

Name	Exposure route	Remark	value
ethyl acetate	fresh water	/	0.24 mg/L
ethyl acetate	water, intermittent release	/	1.65 mg/L
ethyl acetate	marine water	/	0.024 mg/L
ethyl acetate	water treatment plant	/	650 mg/L
ethyl acetate	fresh water sediment	dry weight	1.15 mg/kg
ethyl acetate	marine water sediment	dry weight	0.115 mg/kg
ethyl acetate	soil	dry weight	0.148 mg/kg
ethyl acetate	secondary poisoning	food	0.2 g/kg
chlorobenzene	fresh water	/	0.032 mg/L
chlorobenzene	marine water	/	0.003 mg/L
chlorobenzene	water treatment plant	/	1.4 mg/L
chlorobenzene	fresh water sediment	dry weight	0.922 mg/kg
chlorobenzene	marine water sediment	dry weight	0.092 mg/kg
chlorobenzene	soil	dry weight	0.166 mg/kg
chlorobenzene	secondary poisoning	food	0.01 g/kg

8.2 Exposure controls

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothes. Do not eat, drink or smoke while working. Do not breathe vapours/aerosols.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

Personal protective equipment

Eye and face protection

Safety glasses with side protection (BS EN ISO 16321-1:2022).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The

selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

Appropriate materials

Skin protection

Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). At high risk of skin exposure chemical suits (BS EN ISO 6530:2005) and boots may be required (BS EN ISO 20345:2022).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard BS EN 137, BS EN 138.

Thermal hazards

No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state

liquid

Colour

colorless

Odour

solvent like

Important health, safety and environmental information

Odour threshold	No information.
Melting point/Freezing point	No information.
Boiling point or initial boiling point and boiling range	No information.
Flammability	No information.
Lower and upper explosion limit	1 vol % 8 vol %
Flash point	24 °C
Auto-ignition temperature	> 200 °C
Decomposition temperature	No information.
pH	No information.
Viscosity	No information.
Solubility	Water: insoluble
Partition coefficient	No information.
Vapour pressure	9 hPa
Density and/or relative density	Density: 0.9 g/cm ³ at 20 °C
Relative vapour density	No information.
Particle characteristics	No information.

9.2 OTHER INFORMATION

Explosive properties

No information.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No information.

10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3 Possibility of hazardous reactions

Vapours and air can form flammable or explosive mixtures.

10.4 Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

10.5 Incompatible materials

Oxidants.

10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

(a) Acute toxicity

For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
xylene	dermal	LD ₅₀	rabbit	/	1700 mg/kg	/	/
xylene	oral	LD ₅₀	rat	/	5000 mg/kg	/	/
xylene	inhalation	LC ₅₀	rat	4 h	4500 ppm	/	/
ethyl acetate	oral	LD ₅₀	rabbit	/	4935 mg/kg	/	/
ethyl acetate	inhalation	LC ₅₀	rat	4 h	1600 mg/l	/	/
ethylbenzene	oral	LD ₅₀	rat	/	3500 mg/kg	/	/
ethylbenzene	dermal	LD ₅₀	rabbit	/	15354 mg/kg	/	/
ethylbenzene	inhalation	LC ₅₀	rat	4 h	17.2 mg/l	/	/
chlorobenzene	inhalation	/	/	/	/	/	Harmful if inhaled.

Additional information

Harmful if inhaled. Harmful in contact with skin.

(b) Skin corrosion/irritation

For components

Name	Species	Time	result	Method	Remark
chlorobenzene	/	/	Irritating to skin.	/	/

Additional information

Causes skin and eye irritation.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation

No information.

Additional information

The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

For components

Name	Type	Species	Time	result	Method	Remark
chlorobenzene	in-vivo mutagenicity	/	/	No evidence of mutagenicity.	/	/
chlorobenzene	in-vitro mutagenicity	/	/	No evidence of mutagenicity.	/	/

(f) Carcinogenicity

For components

Name	Exposure route	Type	Species	Time	value	result	Method	Remark
ethylbenzene	/	/	/	/	/	IARC 2B: Possibly carcinogenic to humans.	/	/
chlorobenzene	/	/	/	/	/	There is no evidence of carcinogenic effects.	/	/

(g) Reproductive toxicity

For components

Name	Reproductive toxicity type	Type	Species	Time	value	result	Method	Remark
chlorobenzene	Effects on fertility	/	/	/	/	No evidence	/	/
chlorobenzene	Developmental toxicity	/	/	/	/	No evidence	/	/

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

For components

Name	Exposure route	Type	Species	Time	Exposure	organ	value	result	Method	Remark
chlorobenzene	oral/inhalation/dermal	-	/	/	/	liver	/	Confusion, agitation and/or excitation. Headache. Unconsciousness.	/	/

Additional information

May cause respiratory irritation.

(i) STOT-repeated exposure

No information.

Additional information

May cause damage to organs through prolonged or repeated exposure.

(j) Aspiration hazard

No information.

Additional information

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

No information.

Interactive effects

No information.

11.2 Information on other hazards

Endocrine disrupting properties

No information.

Other information

No information.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute (short-term) toxicity

For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
xylene	EC ₅₀	7.4 mg/L	48 h	crustacea	<i>Daphnia magna</i>	/	/
chlorobenzene	LC ₅₀	10 - 100	96 h	fish	/	/	/

Chronic (long-term) toxicity

No information.

12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

For components

Name	Type	Rate	Time	Evaluation	Method	Remark
ethylbenzene	Water solubility	1000 - 10000 mg/L	/	quickly biodegradable	/	/

12.3 Bioaccumulative potential

Partition coefficient

For components

Name	Media	value	Temperature °C	pH	Concentration	Method
ethylbenzene	Octanol-water	3.6	/	/	/	/

Bioconcentration factor (BCF)

No information.

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

No information.

12.5 Results of PBT and vPvB assessment

No evaluation.

12.6 Endocrine disrupting properties

No information.

12.7 Other adverse effects

No information.

12.8 Additional information

For product

Product is not classified as dangerous for environment. Do not allow to reach ground water, water courses or sewage system.

For components

chlorobenzene

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May accumulate in soil and water systems. Immiscible with water and will sediment in water systems. This substance is not considered to be persistent, bioaccumulative and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulative (vPvB).

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / Packaging disposal

Waste chemical

Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Waste codes / waste designations according to LoW

No information.

Packaging

Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents. Uncleaned containers should not be perforated, cut or welded. Empty containers represent a fire hazard as they may contain flammable product residues and vapour.

Waste codes / waste designations according to LoW

No information.

Waste treatment-relevant information

No information.





Sewage disposal-relevant information

No information.

Other disposal recommendations

No information.

SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
14.1 UN number or ID number			
UN 1263	UN 1263	UN 1263	UN 1263
14.2 UN proper shipping name			
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)			
3	3	3	3
			
14.4 Packing group			
III	III	III	III
14.5 Environmental hazards			
NO	NO	NO	NO
14.6 Special precautions for user			
Limited quantities 5 L Special provisions 163, 367, 650 Packing Instructions P001, IBC03, LP01, R001 Special packing provisions PP1 Transport category 3 Tunnel restriction code (D/E)	Limited quantities 5 L EmS F-E, S-E Flash point 24 °C	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y344 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 10 L Packing Instructions (Pkg Inst) 355 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 L Cargo Aircraft Only, Packing Instructions (CAO, Pkg Inst) 366 Special provisions A3, A72, A192 ERG code 3L	Limited quantities 5 L
14.7 Maritime transport in bulk according to IMO instruments			
	Goods may not be carried in bulk in bulk containers, containers or vehicles.		

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2020/878)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)
not applicable

Ingredients according to Regulation (EC) No 648/2004 on detergents
No information.

Special instructions

Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION**Indication of changes**

8.2 Exposure controls

Key literature references and sources for data

No information.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
 ADR - Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 CEN - European Committee for Standardisation
 C&L - Classification and Labelling
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 CAS# - Chemical Abstracts Service number
 CMR - Carcinogen, Mutagen, or Reproductive Toxicant
 CSA - Chemical Safety Assessment
 CSR - Chemical Safety Report
 DMEL - Derived Minimal Effect Level
 DNEL - Derived No Effect Level
 DPD - Dangerous Preparations Directive 1999/45/EC
 DSD - Dangerous Substances Directive 67/548/EEC
 DU - Downstream User
 EC - European Community
 ECHA - European Chemicals Agency
 EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
 EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
 EEC - European Economic Community
 EINECS - European Inventory of Existing Commercial Substances
 ELINCS - European List of notified Chemical Substances
 EN - European Standard
 EQS - Environmental Quality Standard
 EU - European Union
 Euphrac - European Phrase Catalogue
 EWC - European Waste Catalogue (replaced by LoW – see below)
 GES - Generic Exposure Scenario
 GHS - Globally Harmonized System
 IATA - International Air Transport Association
 ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
 IMDG - International Maritime Dangerous Goods
 IMSBC - International Maritime Solid Bulk Cargoes
 IT - Information Technology
 IUCLID - International Uniform Chemical Information Database
 IUPAC - International Union for Pure Applied Chemistry
 JRC - Joint Research Centre
 Kow - octanol-water partition coefficient
 LC50 - Lethal Concentration to 50 % of a test population
 LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
 LE - Legal Entity
 LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
 LR - Lead Registrant
 M/I - Manufacturer / Importer
 MS - Member States

MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 + H332 Harmful in contact with skin or if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.